Slimin & TOP

R1234yf

cosmotec

your cooling solutions



SLIM IN CDY

Cooling Capacity: 500 - 4000 W
XCB electronic controller with display
Flush-mounted, semi-flush-mounted, or external installation
Quick electrical connections
Sequencing and Modbus connection
Microchannel condenser (from CDY14 onwards)
Condensate evaporator (from CDY14 onwards)
General alarm contacts and remote control
Gasket pre-installed on the air conditioner
Operation up to an ambient temperature of +60°C
CE Certification

TOP ETY

Cooling Capacity: 330 - 5000 W
Condensate evaporator included from model ETY14 onwards
Quick connections (except ETY03)
ECB digital thermostat (except ETY03)
General alarm contacts and remote control supplied as standard (except ETY03)
CE Certification

SLIMIN CDY

Code		CDY05	CDY10	CDY14	CDY20	CDY30	CDY40
Cooling Capacity	@230V,50Hz/@ 400V,50Hz CVH60	600	900	1400	2100	3100	4000
Power Supply	[V,~,Hz]	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	
				400,2,50 460,2,60	400,3,50 460,3,60	400,3,50 460,3,60	400,3,50 460,3,60
Dimensions	(AxLxP)	956x375x196	956x375x196	1666x454x181	1666x454x181	1666x496x221	1666x496x256

TOP ETY

Code		ETY03	ETY06	ETY09	ETY14	ETY20	ETY28	ETY41	ETY60
Cooling Capacity	@230V,50Hz/@ 400V,50Hz CVH60	330	600	875	1400	2000	3000	3800	5200
Power Supply	[V,~,Hz]	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	
			400,2,50 460,2,60	400,2,50 460,2,60	400,2,50 460,2,60	400,2,50 460,2,60	400,3,50 460,3,60	400,3,50 460,3,60	400,3,50 460,3,60
Dimensions	(AxLxP)	180x476x324	335x600x325	335x600x325	450x600x400	450x600x400	480x800x450	480x800x450	550x800x600

STULZ S.p.A. - Via E.Torricelli 3 - 37067 Valeggio sul Mincio (VR) - Tel. +39 045.6331600 - info@cosmotec-cooling.com - **www.cosmotec.it**