Protherm
R1234yf

cosmotec
your cooling solutions



Cooling Capacity
300 - 6000 W

Electronic Controller
XCB + display (except CVY03;
display available as an accessory for CVH)

CE Certification

Sequencing and Modbus
(with dedicated accessories)

Condensate Evaporator
from CVY11 onwards

Quick Connections
(CE versions, except CVY03)

Microchannel Condenser
(from CVY/CVH11 onwards)

Standard General Alarm Contacts and Remote Control
(except CVY03)

PROTHERM INDOOR CVY

Code		CVY03	CVY05	CVY08	CVY11	CVY15	CVY20	CVY30	CVY40	CVY60
Cooling Capacity	@230V,50Hz/@ 400V,50Hz CVH60	310	525	800	1000	1500	2000	3200	3900	5800
Power Supply	[V,~,Hz]	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	
			400,2,50 460,2,60	400,2,50 460,2,60	400,2,50 460,2,60	400,2,50 460,2,60	400,3,50 460,3,60	400,3,50 460,3,60	400,3,50 460,3,60	400,3,50 460,3,60
Dimensions	(AxLxP)	443x325x206	642x315x221	642x315x221	913x413x248	913x413x248	1005x413x263	1219x514x347	1219x514x347	1406x556x403

PROTHERM OUTDOOR CVH

Code		CVH05	CVH08	CVH11	CVH15	CVH20	CVH40	CVH60
Cooling Capacity	@230V,50Hz/@ 400V,50Hz CVH60	525	800	1000	1500	2000	3900	5800
Power Supply	[V,~,Hz]	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	230,1,50/60	
		400,2,50 460,2,60	400,2,50 460,2,60	400,2,50 460,2,60	400,2,50 460,2,60	400,3,50 460,3,60	400,3,50 460,3,60	400,3,50 460,3,60
Dimensions	(AxLxP)	636x315x233	636x315x233	906x413x272	906x413x272	999x413x286	1211x514x370	1399x556x428

STULZ S.p.A. - Via E.Torricelli 3 - 37067 Valeggio sul Mincio (VR) - Tel. +39 045.6331600 - info@cosmotec-cooling.com - **www.cosmotec.it**